



PDC® F-950

EVA Foam Primer FOR INDUSTRIAL USE ONLY

DESCRIPTION:

F-950 EVA Foam Primer is an air dry EVA solvent based primer which has been specifically formulated to increase adhesion of Muraculon spray coatings to EVA foams. F-950 EVA Foam Primer is especially effective in increasing adhesion to fusion molded and normally fabricated EVA foams.

F-950 EVA Foam Primer is used in manufacturing of patient positioning products, athletic padding and industrial applications.

SPECIFICATIONS:

Solids: (wt.) 18%

Shelf life: 1+ years at 77°F unopened container

Coverage: 200 sq ft/ gallon

Finish/ color: amber

SURFACE PREPARATIONS:

MIX WELL BEFORE USE.

All surfaces to be coated must be free of any oils, dust or loose foam particles.

USE ADEQUATE VENTILATION.

SPRAYING: SHEER MIX BEFORE SPRAYING.

Siphon Cup Gun/ Pressure pot sprayers may be used.

Apply light [damp] overlapping coats, holding gun 6"-12" from surface, using 4"-6" pattern. Be sure to coat the entire surface and allow to dry 30 minutes minimum or until tacky to touch before applying Muraculon Coating.

RECOMMENDED EQUIPMENT AND SETTINGS:

Binks® model 2100 gun

Material: 20psi

Nozzle: 63B

Atomization: 10-25psi

Cap: 63PB

Dilution: not recommended

Needle: 363A

Clean up: Toluene

We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the applications of this information or the safety and suitability of our products, either alone or in combination with other product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products whether used alone or in combination with other products. Ever changing V.O.C. regulations in your area may require you to contact local authorities for proper use and/or disposal of this product. Should you need further assistance, please contact PLASTI DIP INTERNATIONAL technical service.

PDC is a registered trademark of PLASTI DIP INTERNATIONAL
Performix and logo are trademarks of PLASTI DIP INTERNATIONAL
BINKS is a registered trademark of BINKS MFG. CO., Franklin Park, IL